

Guidance on class rule c.4.1, c.4.3 and c.10.3 (b) & (c) - Placement of Class Insignia, numbers national flag and sponsors logos

Instructions on the positioning of characters on sails.

Positioning sail numbers & national letters

- 1 Lay the mainsail starboard side down
- 2 Stick a line of masking tape a minimum of 60mm up and parallel to the batten (3rd one down); this keeps the numbers parallel to the batten.
- 3 Measure a minimum of 60mm from the leach and fix the first character on the sail.
- 4 Measure a minimum of 60mm from the fixed character and fix the next character on the sail. Repeat until the full sail number (including national letters) are fixed. NOTE: All characters must be separated by at least 60mm.
- 5 Once you have finished the Port side, turn the mainsail over.
- 6 Stick a line of masking tape on the Starboard side a minimum of 60mm above the characters on the port side (the characters on the starboard side must be highest).
- 7 Measure a minimum of 60mm from the leach and fix the first character on the sail.
- 8 Measure a minimum of 60mm from the fixed character and fix the next character on the sail. Repeat until the full sail number (including national letters) are fixed. NOTE: All characters must be separated by at least 60mm.
- 9 Your sail should look like the sail below.

Positioning national flag

- 10 Measure a minimum of 60mm from the leach and batten and fix the flag on each side of the sail.

